

GC1700 SERIES  
Sub Compacts

MODELS
ENGINE
Engine HP
PTO HP
Rated engine speed (RPM)
Type
Displacement in. <sup>3</sup> (cc)
Cooling system
DRIVETRAIN
Hydrostatic
Forward speeds with R1 tires mph (kph)
Rear breaks
Rear PTO type
Mid PTO type
HYDRAULICS
Type of system
Power steering flow gpm (lpm)
Total flow gpm (lpm)
Factory joystick
ASABE hitch
Rate of drop control
Lift capacity @ hitch point lbs. (kg.)
Type of stabilizers
Type of link ends
OPERATOR'S AREA
Platform ROPS
Seat type
Seat belt type
Hood type
DIMENSIONS
Overall length in. (mm)
Max width @ rear combo light in. (mm)
Max height over ROPS in. (mm)
Ground clearance in. (mm)
Wheelbase in. (mm)
Shipping weight lbs. (kg.)
Fuel tank capacity gal. (L)

GC1705	GC1710	GC1715	GC1720
22.5	22.5	25	25
18.7	18.7	19.6	19.6
2,600	2,600	3,000	3,000
Tier 4 Final, 3-cylinder diesel	2-side Tier 4 Final, 3-cylinder diesel	Tier 4 Final, 3-cylinder diesel	Tier 4 Final, 3-cylinder diesel
68.5 (1,123)	68.5 (1,123)	68.5 (1,123)	68.5 (1,123)
Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled
2 Range w/cruise	2 Range w/cruise	2 Range w/cruise	2 Range w/cruise
0-9.1 (0-14.7)	0-9.1 (0-14.7)	0-9.1 (0-14.7)	0-9.1 (0-14.7)
Wet disc	Wet disc	Wet disc	Wet disc
Independent 540 RPM	Independent 540 RPM	Independent 540 RPM	Independent 540 RPM
Independent 2,000 RPM	Independent 2,000 RPM	Independent 2,000 RPM	Independent 2,000 RPM
Open Center	Open Center	Open Center	Open Center
2 (7.5)	2 (7.5)	2 (7.5)	2 (7.5)
6.3 (24.0)	6.8 (26.3)	6.8 (26.3)	6.8 (26.3)
Opt.	Std.	Std.	Std.
Cat. I	Cat. I	Cat. I	Cat. I
Std.	Std.	Std.	Std.
1,190 (540)	1,190 (540)	1,190 (540)	1,190 (540)
Turnbuckle	Turnbuckle	Turnbuckle	Turnbuckle
Fixed	Fixed	Fixed	Fixed
Fixed	Folding	Fixed	Folding
Coil spring	Coil spring / reversible	Coil spring	Coil spring / reversible
Retractable	Retractable	Retractable	Retractable
Steel, forward-tilting	Steel, forward-tilting	Steel, forward-tilting	Steel, forward-tilting
97.6 (2,480)	177 (4,496)	97.6 (2,480)	177 (4,496)
47.25 (1,200)	53.94 (1,370)	47.25 (1,200)	53.94 (1,370)
72.8 (1,850)	86 (2,185)	72.8 (1,850)	86 (2,185)
6.7 (170)	6.7 (170)	6.7 (170)	6.7 (170)
57.1 (1,450)	57.1 (1,450)	57.1 (1,450)	57.1 (1,450)
1,433 (650)	2,670 (1,211)	1,433 (650)	2,670 (1,211)
6.6 (25)	6.6 (25)	6.6 (25)	6.6 (25)