

SPECIFICATIONS*

MODEL	1526
ENGINE	
Gross engine HP (kW)	24.8 (18.5)
PTO HP HST (kW)	20.1 (15)
Rated engine speed	2,600
Type	3-cylinder diesel
Displacement in. ³ (L)	91.4 (1.5)
Cooling system	Liquid cooled
Fuel tank capacity gal. (L)	7.1 (27)
TRANSMISSION	
Hydrostatic w/ cruise	3-Range
Rear brakes	Wet, multiple disc
PTO	
Rear PTO type	Independent 540 RPM
Control	Electro-hydraulic
Mid PTO type – Opt.	2,000 RPM
HYDRAULICS	
Type of system	Open center
Flow at remotes gpm (LPM)	5.5 (20.9)
Power steering flow gpm (LPM)	3.2 (12.3)
Total flow gpm (LPM)	8.7 (33.2)
Rear Remote Valves	2 Opt.
3-POINT HITCH	
ASAE hitch	Cat. 1
Controls	Position
Rate of drop control	Std.
Lift capacity @ hitch point lbs. (kg.)	1,322 (600)
Lift capacity @ 24" behind lbs. (kg.)	992 (450)

MODEL	1526
OPERATOR AREA	
Platform type	Semi-flat ISO mounted
ROPS	Foldable
Seat type	Suspended with retractable seatbelt
DIMENSIONS WITH R4 TIRES	
Overall length in. (mm)	111 (2,820)
Min. overall width in. (mm)	55.1 (1,400)
Max. height over ROPS in. (mm)	96.1 (2,440)
Ground clearance in. (mm)	11.6 (295)
Wheelbase in. (mm)	61.4 (1,560)
Base weight lbs. (kg.)	2,077 (942)
LOADER	
Max. lift height @ pivot pin in. (mm)	83 (2,108)
Dump angle	42°
Rollback angle	31°
Lift capacity to full height @ 19.5" forward lbs. (kg.)	852 (386)
Breakout force @ 19.5" forward lbs. (kg.)	1,282 (582)
Bucket options (in.)	54
MID-MOUNT MOWER	
Discharge type	Right side discharge
Cutting width in. (mm)	60 (1,524)
Cutting height in. (mm)	1.5-4.0 (38-102)
Number of blades	3
Max blade tip velocity ft/sec. (m/sec.)	320.2 (97.6)

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.



For information, please visit

www.masseyferguson.us