

SPECIFICATIONS*

MODEL	MF4707	MF4708	MF4709	MF4710
ENGINE				
Max engine power HP (kW) @ 2,000 RPM	75 (55.9)	85 (63.4)	95 (70.8)	100 (74.6)
Rated engine HP (kW)	70 (52.2)	80 (59.6)	90 (67.1)	100 (74.6)
Rated engine speed	2,200 RPM			
PTO HP (kW)	57 (42.5) @ 2,200 RPM 63 (46.9) @ 2,000 RPM	67 (49.9) @ 2,200 RPM 73 (54.4) @ 2,000 RPM	77 (57.4) @ 2,200 RPM 81 (60.4) @ 2,000 RPM	88 (65.6) @ 2,200 RPM 88 (65.6) @ 2,000 RPM
Engine	AGCO Power 3-cyl, 3.3 L, intercooled turbocharged, high-pressure common-rail direct fuel injection (HPCR)			
Emissions control; EPA Tier 4-compliant	Diesel Oxidation Catalyst (DOC), Exhaust Gas Recirculation (EGR)	SCR technology (post-combustion DEF), diesel oxidation catalyst (DOC)		
DRIVETRAIN				
Transmission type	12F x 12R, 2-range, power shuttle, electrohydraulic shuttle lever or opt. Dyna-2 powershift			
Clutch	Wet clutch with easy shift knob and electrohydraulic power shuttle lever			
Rear axle	Flange-type with internal planetary final drives			
Brakes	4 wheel disc brakes, independently controlled via foot pedals			
Differential lock	Rear axle engaged via electrohydraulic rocker switch			
Front axle	2WD or 4WD heavy-duty front axle			
DIMENSIONS				
Wheelbase in. (mm)	88.5 (2,250)			
Minimum width in. (mm)	Std. radial tires—rear 420/85R30, 60.3 (1,533)			
Base weight without ballast lbs. (kg.)	2WD ROPS: 7,478 (3,392); 2WD Cab: 8,294 (3,762) 4WD ROPS: 7,734 (3,508); 4WD Cab: 8,644 (3,921)			
Fuel capacity gal. (L)	27.7 (105), ground fill with metal fuel-tank guard			
HYDRAULICS				
Hydraulic system	Open center system, single pump			
Hydraulic flow @ rear remotes gpm (lpm)	17.7 (67)			
Rear remote valves	2 valves standard with (DA, KO, FL) 3rd valve optional with (DA, KO, FL, FD)			
Loader joystick	Optional integrated factory installed joystick			
3-pt. lift capacity lbs. (kg.) full stroke @ 24" (610 mm) behind ball ends	Category II, 4,850 (2,200)			
Rear PTO	Independent, electro-hydraulic engagement via switch, 540/540E Std., 540/1000 Opt.			
OPERATOR'S AREA				
Electrical system	12-volt DC system, 80-amp alternator, 7-pin trailer socket, 30-amp auxiliary power socket Std.			
Platform features	Semi-platform deck, folding ROPS, rubber mat, toolbox, L & R shields, grab handles			
Lighting (ROPS)	4 headlights, 2 rear signal/hazard lights, 1 rear ROPS work light; 2 mid-mount adjustable work lights			
Std. Steering	Cab = tilt and telescopic steering Platform = Tilt steering			
Std. Seat	MF 4700 Series cab = mechanical swiveling seat with armrests (air-ride swivel seat optional) MF 4700 Series platform = mechanical spring suspension seat with armrests			

