

BALER MODEL	1734	1745	2946/2946A	2956/2956A
<b>Bale Size</b>				
Width: in. (mm)	39 (991)	46.5 (1,181)	46.5 (1,181)	61.5 (1,562)
Diameter – max. in. (mm)	52 (1,321)	62 (1,575)	72 (1,829)	72 (1,829)
Weight* (dry) lbs. (kg.)	550 (249)	1,250 (567)	up to 1,644 (746)	up to 2,200 (998)
<b>Dimensions &amp; Weights</b>				
Overall width: in. (mm)	74.5 (1,892)	92.5 (2,350)	101.5 (2,578); without gauge wheels 101 (2,565)	116.5 (2,959); without gauge wheels 116 (2,946)
Overall length: in. (mm)	132 (3,353)	147 (3,734)	163.5 (4,153)	163.5 (4,153)
Overall height: in. (mm)	84 (2,134)	101 (2,565)	121 (3,073)	121 (3,073)
Weight: lbs. (kg.)	2,780 (1,261)	3,720 (1,687)	6,075 (2,756)	6,500 (2,948)
Tongue weight (empty): lbs. (kg.)	500 (227)	440 (200)	1,760 (798)	1,760 (798)
Tire size	7.60 x 15	31L x 13.5-15 Std. 14L x 16.1 Opt.	21.5L x 16.1	21.5L x 16.1
<b>Bale Chamber</b>				
Number of belts	5 laced, mini rough top	6 laced, wedge grip pattern	6 laced, wedge grip pattern	8 laced, wedge grip pattern
Belt width: in. (mm)	4.8 (122)	7.0 (178)	7.0 (177)	7.0 (177)
Bale size indicator	Visual gauge	Visual gauge	On C1000	On C1000
Bale shape indicator	NA	Optional	On C1000	On C1000

\*Depends on crop and moisture conditions



AGCO may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. Attention: Photographs in this publication may show protective shields and guards open or removed for the purposes of illustration. Be certain all shields and guards are in place during operation.

BALER MODEL	1734	1745	2946/2946A	2956/2956A
<b>Pickup</b>				
Width				
Tine to tine: in. (mm)	33.8 (858)	44.2 (1,122)	65.0 (1,651)	80.6 (2,046)
Inside, panel to panel: in. (mm)	38.0 (965)	46.8 (1,188)	67.6 (1,717)	82.6 (2,098)
Outside end to end: in. (mm)	38.8 (986)	46.8 (1,188)	83.7 (2,126)	98.7 (2,507)
Tines bars	3	4	4	4
Number of tines	42	72	104	128
Windguard	Rod	Adjustable rod	Optional solid, Optional roller	Optional solid, Optional roller
<b>Bale Wrapping</b>				
Twine Wrapping	Manually-rope electric actuated optional	Electric actuated (Auto-Tie optional)	Auto-Tie- electric actuated	Auto-Tie- electric actuated
Number of twine balls	2	4	Up to 12	Up to 12
Mesh wrap	NA	Factory option	Factory option	Factory option
<b>Tractor Requirements</b>				
Minimum PTO HP (kW)	30 (22)	40 (30)	65 (48)	70 (52)
Tractor weight (min) lbs. (kg.)	3,000 (1,361)	4,000 (1,814)	6,000 (2,721)	7,000 (3,175)
PTO speed (RPM)	540	540	540 or 1,000	540 or 1,000
Hydraulic remote valves	One double acting	One double acting	Two double acting; one double acting (for 2946A)	Two double acting; one double acting (for 2956A)
<b>Optional Kits</b>				
	Gathering wheels Bale ramp Fire extinguisher Twine threader	Gathering wheels Bale ramp Fire extinguisher Twine threader Mesh wrap Bale kicker Bale counter	Bale ramp Fire extinguisher Twine threader Mesh wrap Hydraulic kicker Silage kit Solid Windguard Roller Windguard Short crop kit Soft-Core kit Light kit	Bale ramp Fire extinguisher Twine threader Mesh wrap Hydraulic kicker Silage kit Solid Windguard Roller Windguard Short crop kit Soft-Core kit Light kit

